YINGJIAO®

YSDN75 SERIES 75W

Yingjiao's metal case power family designed with slim housing and for full range AC input from 90V AC to 264V AC.
The series are single phase PSU, providing adjustable DC output voltage. They have high efficiency and operate in wide temperature range.
The series can widely used for industrial automation & control systems, varied equipments etc.

Features

- DC O/P Voltage Adjustable
- Universal AC Input 90-264V
- Protection:Short Circuit/Overload /Over Voltage/Over Temperature
- Free Air Convection Design
- Installation:DIN Rail TS-35/7.5 & 15
- Three Years Warranty

Model Information

Yingjiao Part number	DC VOLTAGE	RATED CURRENT (Max.)	RATED POWER	VOLTAGE ADJ. RANGE
YSDN75-12	12V	6.3A	75.6W	12-14V
YSDN75-24	24V	3.2A	76.8W	24-28V
YSDN75-48	48V	1.6A	76.8W	48-55V

Input

RATED INPUT (Certified Voltage)	100 ~ 240VAC	
NOMINAL INPUT VOLTAGE RANGE	90~ 264VAC or 127-370VDC [DC input by connecting AC/L(+),AC/N(-)]	
FREQUENCY RANGE	47~63Hz	
EFFICIENCY (Typ.)	85.50%	YSDN75-12
	88.00%	YSDN75-24
	88.00%	YSDN75-48
AC CURRENT (Typ.)	1.45A/115VAC	
	0.9A/230VAC	
INRUSH CURRENT (Typ.)	20A/115VAC	
	35A/230VAC	
LEAKAGE CURRENT	<1mA / 240VAC	

Output

RIPPLE & NOISE (max.)	80mVp-p	YSDN75-12
	120mVp-p	YSDN75-24
	150mVp-p	YSDN75-48
VOLTAGE TOLERANCE	±2.0%	
LINE REGULATION	±0.5%	
LOAD REGULATION	±1.0%	
SETUP, RISE TIME	1200ms, 60ms/230VAC at full load	
	2000ms, 60ms/115VAC at full load	
HOLD UP TIME (Typ.)	60ms/230VAC at full load	
	12ms/115VAC at full load	

Protection

OVER LOAD	105 ~ 130% rated output power Protection type: Hiccup Mode- recovers automatically after fault condition is removed
OVER VOLTAGE	14~17V YSDN75-12 29 ~ 33V YSDN75-24 56 ~ 65V YSDN75-48 Protection type : Shut down o/p voltage, re-power on to recover
OVER TEMPERATURE	Protection type : Shut down o/p voltage, re-power on to recover

Environment

WORKING TEMP.	-20 ~ +70℃ (Refer to "Derating Curve")
WORKING HUMIDITY	20 ~ 95% RH non-condensing
STORAGE TEMP.	-40 ~ +85℃, 10 ~ 95% RH
STORAGE HUMIDITY	10 ~ 95% RH
MTBF	450K hrs min. MIL-HDBK-217F (25℃)

SAFETY & EMC

SAFETY STANDARDS	UL508, BS/EN62368-1
WITHSTAND VOLTAGE	I/P-O/P:3KVAC I/P-FG:2KVAC O/P-FG:0.5KVAC
ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG:>100M Ohms / 500VDC / 25℃ / 70% RH
EMC EMISSION	Compliance to BS EN/EN55032 , BS EN/EN61000-3-2,-3
EMC IMMUNITY	Compliance to BS EN/EN61000-4-2,3,4,5,6,8,11, BS EN/EN55035, BS EN/EN61000-6-2 (BS EN/EN50082-2),

Note

1.All parameters NOT specially mentioned at 230VAC input, rated load and 25℃ of ambient temperature.

2.Ripple&noise are measured from peak to peak with band width limit of 20MHz(0.1uF and 47uF/50V parallel capacitor under DC output full load,AC nominal input 25℃ ambient temperature).

3.Installation clearances: top with 40mm, bottom with 20mm, left and right with 5mm. Increase the space to 10-15mm when the adjacent device is heat source.

4.Derating may be needed under low input voltage. Please check the derating curve for more details.

5.Efficiency test after 30 minutes of burn-in.

6.The ambient temperature derating of 3.5 ℃/1000m for operating altitude higher than 2000m(6500ft).

Dimensions & Weight

Width:	32mm / 1.26in
Height:	125mm / 4.92in
Depth:	100.5mm / 3.96in
Weight:	0.51kg

Packing

Carton Size:	31.5 x 30 x 30 CM 12.4 x 11.8 x 11.81 in
Master Carton Quantities:	20pcs / Carton

Mechanical Specification

Input

No.	Description
1	FG ⏚
2	AC/N or DC -
3	AC/L or DC +

Output

No.	Description
1,2	DC OUTPUT -V
3,4	DC OUTPUT+V

Block Diagram

Deduction Curve and Temperature

Minus Output and Input Voltage Curves

CONEXA
TECH SOLUTIONS

Want to know more?

For sales, technical support or additional information please get in touch with our team of experts.

ADDITIONAL SERVICES

We provide an end-to-end service

From the initial consultation and sourcing unique components to supplying bespoke solutions including a full design and build process.

Bespoke services

Customised and curated technology solutions across the full range of Conexa Tech products

Sourcing

A full suite of electronics, cable, and mechanical sourcing capabilities

Design & Build

Development and manufacturing services

hello@conextech.com | +44 118 402 3430

CONEXATECH.COM